

## Model Info | Load Charts

# SKY TRAK 10054 LEGACY MODEL INFORMATION

### Engine

Cummins 4BTA3.9 Turbo After Cooled Diesel  
116 HP (87 kW) @ 2500 RPM (U/Min)  
Torque rating 300 lb. ft. (407 Nm) @ 1600 RPM

### Transmission

Modulated powershift, 4-speed forward and 3-speed reverse.

### Axles and Brakes

Full-time planetary 4-wheel drive with inboard mounted internal wet disc brakes.

### Boom

Telescopic 4-stage welded box section construction using high strength low alloy steel.  
Replaceable high density wear pads, to limit friction, with wear indicators.

### Operating Specs

Max lift capacity	10,000 lbs. (4540 kg)
Lift height	53'2" (16,2 m)
Max reach below grade	4'11" (1,4 m)
Curb weight	27,323 lbs. (12,405 kg)
Hydraulic oil capacity	60 gal. (227 liters)
Fuel tank capacity	35 gal. (132 liters)
Standard tires (air filled)	17.5 x 25, 12 ply
Frame tilt to left or right	10°
Top speed	20 mph

### Standard Equipment

- TRAK-Attach system
- Auxiliary hydraulics
- Automatic fork leveling system
- Frame leveling
- Load holding valves on frame level, stabilizer, attachment tilt, extend and lift cylinders
- Oscillating rear axle with Stabil-TRAK stabilization system
- Boom extend/outrigger interlock system
- Variable flow, load sensitive hydraulic system
- 2-wheel, 4-wheel and crab steering
- Hydraulically actuated in board wet disc brakes

- Emergency brake with transmission declutch feature
- ROPS/FOPS operator cab
- Deluxe suspension seat with retractable seat belt
- Dual Joystick controls
- Steering wheel mounted horn and backup alarm
- Instrument cluster with gauges and warning lights
- 12 V electrical system
- Lockable doors, covers and tool box
- Engine block heater
- Rear view mirrors
- High clearance front outriggers

### Options

- Enclosed all weather cab
- Basic work lights
- Complete road lights
- Rotating Beacon
- Fenders
- Soft cab enclosure
- Overnight cab cover
- Cold start package

### Attachments

- Standard carriages: 48" (1,22 m), 60" (1,52 m) and 72" (1,83 m)
- $\pm 10^\circ$  side tilt carriages: 48" (1,22 m), 60" (1,52 m) and 72" (1,83 m)
- $\pm 45^\circ$  swing carriages: 52" (1,32 m) and 72" (1,83 m)
- 48" (1,22 m) pallet forks
- 60" (1,52 m) lumber forks
- 48" (1,22 m) block forks
- Wallboard/Sheet material handler
- 15' (4,57 m) truss boom
- 96" (2,44 m) windrow broom
- Utility bucket
- Concrete bucket
- Hydraulic earth auger

  
**BACK TO TOP**