

Model Info | Load Charts

SKY TRAK 4266

MODEL INFORMATION

Engine

Cummins 4BT3.9 - C110 Turbocharged Diesel Engine.
 110 HP (82 kW) @ 2500 RPM (u/min)
 Torque rating 293 lb. ft. (397 Nm) @ 1500 RPM

Transmission

Powershift, 4-speeds forward and 3-speeds reverse.

Axles and Brakes

Full-time planetary 4-wheel drive with inboard wet disc brakes and integrated park brake.

Boom

Telescopic 3-stage welded box section construction using high strength low alloy steel. Replaceable high density wear pads with wear indicators.

Operating Specs

Max. lift capacity	6,600 lbs. (3000 kg) @ 24" (610 mm) Load Center
Max. lift height	42'4" (12,9 m)
Max. forward reach	29'4" (7,5 m)
Max. reach below grade	1'5" (0.43 m)
Operating weight	23,500 lbs. (10659 kg)
Hydraulic oil capacity	28.5 gal. (108 liters)
Fuel tank capacity	33.5 gal. (127 liters)
Standard tires	13.00 x 24, 16 ply
Frame tilt to left or right	10°

Standard Equipment

Structural Features

- Unitized Tubular Steel Frame
- Frame Leveling - 10° Tilt Right or Left
- Telescopic 3-section Boom
- Replaceable High Density Wear Pads
- TRAK-Attach System for Multi-Tool Applications
- Oscillating Rear Axle with Stabil-TRAK[®] Load Placement System

Performance Features

- Liquid Cooled Diesel Engine
- 4-Speed Powershift Transmission
- 2-Wheel Front, 4-Wheel, and Crab Steering
- Engine Block Heater
- Planetary Front and Rear Axles with Hydraulically Actuated Inboard Wet Disc Brakes
- All Terrain 13.0 x 24 Lug Type Pneumatic Tires (16 Ply Minimum)
- Load Holding Valves - Frames Level, Attachment Tilt, Boom Hoist and Extend Cylinders
- 250 Hour Service and Grease Intervals
- Automatic Fork Leveling System
- 35 GPM (132 l/min) Single Section Load Sensing Hydraulic Pump
- 12 Volt Electrical System
- Single 12 Volt (1000 CCA) Battery
- 30 Gallon (114 liter) Fuel Tank

Operator Features

- ROPS/FOPS Operator Cab
- Hydraulic and Air Filter Restriction Warning Lights
- Warning Lights and Audible Alarms on Key Machine Functions
- Single multi-functional Hydraulic Joystick Control
- Deluxe Tilt Steering Wheel with Center Mounted Horn
- Park Brake with Transmission Declutch Feature
- Frame Level Indicator
- Back Up Alarm
- Anti-Vandal Protection
- Rear View Mirrors
- Adjustable Deluxe Suspension Seat with Retractable Seat Belt
- Walkup Serviceability

Options

- Fenders
- Fully Enclosed Cab with Heater, Defroster, Windshield and Roof Wipers/Washer
- Air Conditioning
- Light Package
- 3" Seat Belt
- Cold Start Package

Attachments

- Standard Carriages: 48" (1,22 m), 60" (1,52 m) and 72" (1,83 m)

- $\pm 10^\circ$ Side Tilt Carriages: 48" (1,22 m), 60" (1,52 m) and 72" (1,83 m) (requires auxiliary hydraulics)
- $\pm 45^\circ$ Swing Carriages: 52" (1,32 m) and 72" (1,83 m) (requires auxiliary hydraulics)
- 48" (1,22 m) Pallet Forks
- 60" (1,52 m) Lumber Forks
- 48" (1,22 m) Block Forks
- Auxiliary Hydraulics
- Sheet Material Handler
- 12' (3,7 m) Truss Boom
- 1 1/4 yard Utility Bucket
- Hydraulic Earth Auger
- Concrete Bucket (manual/hydraulic)


BACK TO TOP