

Model Info | Load Charts

SKY TRAK 4290 MILLENNIA MODEL INFORMATION

Engine

Cummins 4BT3.9 Turbo Diesel Engine.
110 HP (82 kW) @ 2500 RPM (U/Min)
Torque rating 293 lb. ft. (397 Nm) @ 1500 RPM

Transmission

Powershift, 4-speeds forward and 3-speeds reverse.

Axles and Brakes

Full-time planetary 4-wheel drive with inboard wet disc brakes and integrated park brake.

Boom

Telescopic 3-stage welded box section construction using high strength low alloy steel. Replaceable high density wear pads with wear indicators.

Operating Specs

Max. lift capacity	9,00 lbs. (4086 kg)
Max. lift height	42'4" (12,9 m)
Max. reach below grade	2'5" (737 mm)
Operating weight	26,455 lbs. (12,011 kg)
Hydraulic oil capacity	28.5 gal. (108 liters)
Fuel tank capacity	33.5 gal. (127 liters)
Standard tires	15.50 x 25, 12 ply
Frame tilt to left or right	10°

Standard Equipment

- TRAK-Attach System
- Automatic fork leveling system
- Frame leveling
- Load holding valves on frame level, attachment tilt, extend and lift cylinders
- Oscillating rear axle with Stabil-TRAK Stabilization System
- 2-wheel front, 4-wheel and crab steering
- Hydraulically actuated inboard wet disc brakes
- Park brake with transmission declutch feature
- ROPS/FOPS operator cab
- Deluxe suspension seat with retractable seat belt
- Single multi-functional hydraulic Joystick control
- Horn and backup system

- 12V electrical system
- Lockable doors and covers
- Engine block heater
- Rear view mirrors
- 250 hour service and grease intervals

Options

- Fenders
- Fully enclosed cab with heater, defroster, windshield and roof wipers/washer
- Air conditioning
- Light package
- Auxiliary hydraulics
- Optional seats
- 3" seat belt
- Cold start package
- Soft cab enclosure
- Rotating beacon
- Transit protection coating

Attachments

- Standard carriages: 48" (1,22 m), 60" (1,52 m) and 72" (1,83 m)
- $\pm 10^\circ$ side tilt carriages: 48" (1,22 m), 60" (1,52 m) and 72" (1,83 m)
- $\pm 45^\circ$ swing carriages: 72" (1,83 m)
- 48" (1,22 m) pallet forks
- 60" (1,52 m) lumber forks
- 48" (1,22 m) block forks
- 12' (3,7 m) truss boom
- 1 1/4 yard utility bucket
- Wallboard handler
- Hydraulic earth auger
- Concrete bucket (manual/hydraulic)


BACK TO TOP