



- ▶ Home
- ▼ Products
  - Overview
  - Skid-Steer Loaders
  - Compact Track Loaders
  - Excavators
  - Attachments
  - Equipment Financing
  - Pricing Information
  - Trade Shows & Fairs
- ▶ Training Resources
- ▶ Dealer Locator
- ▶ WorkSaver
- ▶ Markets
- ▶ Bobcat Story
- ▶ Media Resources
- ▶ Contacts
- ▶ Bobcat Store
- ▶ Employment
- ▶ Frequently Asked Questions



LOADER SPECIFICATIONS

Model	450C-Series
Year	1994 - 1998
Engine Manufacturer	Kohler
Engine Model	M-18QS
Fuel Type	Gas
Cooling Type	Air
Displacement	42.19 Cu.In.
Horsepower	16.5 HP @ 3000 RPM
Cylinders	2
Operating Weight	2195 Lbs.
Rated Operating Capacity	600 Lbs.
Tipping Load	1217 Lbs.
Travel Speed (MPH)	0-5.2 Low/High
Hydraulic Pump Capacity	6.8 Low/High
Hydraulic System Relief	1400 PSI
Transmission	Hydrostatic Type
Length w/Std. Bucket	97.2 In.
Width w/Std. Bucket	35.5 In.
Height (Top of Cab)	71.5 In.
Height to Hinge Pin	92.4 In.
Reach at Max Height	15 In.
Dump Angle	38 Degrees
Ground Clearance	5.9 In.
Angle of Departure	26 Degrees
Rollback Angle	25 Degrees

Wheelbase 28.4 In.

Tread 29.4 In.

Steering Controls Dual Levers

Hydraulic Controls Dual Pedals

Cylinders: Lift (In.) 2 Bore 1 Rod 21.88 Stroke

Cylinders: Tilt (In.) 3 Bore 1.25 Rod 10.94 Stroke

Tires 5.70x12

Auxillary Hydraulics Opt.

Lights Opt.

Parking Brake Std.

Bobcat Interlock Control System Std.

Attachments: Backhoe N/A

Attachments: Hookup (Bob-Tach or Pin-On) Bob-Tach/Pin-On

**Back**



P.O. Box 6000, West Fargo, ND 58078-6000  
Send us your [Questions & Comments](#).  
Technical Comments: [webmaster](#)  
© Bobcat Company 1997-2001