

Model Info | Load Charts

SKY TRAK 5028 & 5028 HI-TORQ MODEL INFORMATION

Engine

Cummins 4B3.9 Diesel
80 HP (57 kW) @ 2500 RPM (U/Min)
Torque rating 184 lb. ft. (250 Nm) @ 1200 RPM

Transmission

Automatic, 3-speed forward, 1-reverse and park.
HI-TORQ model equipped with dual range
gearbox, 6-speed forward, 2-reverse and park.

Axles and Brakes

Full-time planetary 4-wheel drive with wheel end wet disc
brakes.

Boom

Telescopic 2-stage welded box section construction using
high strength low alloy steel.
Replaceable high density wear pads, to limit friction, with
wear indicators.

Operating Specs

Max lift capacity	5000 lbs. (2270 kg)
Lift height	27'8" (8,4 m)
Max reach below grade	2' (0,6 m)
Curb weight	14,300 lbs. (6492 kg)
Hydraulic oil capacity	27 gal. (102,2 liters)
Fuel tank capacity	24 gal. (91 liters)
Standard tires	15.00 x 19.5, 12 ply
Frame tilt to left or right	8°

Standard Equipment

- TRAK-Attach system
- Automatic fork leveling system
- Frame leveling
- Load holding valves on frame level, attachment tilt, extend and lift cylinders
- Hydraulic oil cooler
- Oscillating rear axle
- 2-wheel, 4-wheel and crab steering
- Hydraulically actuated wet disc brakes
- Parking brake
- FOPS operator cab
- Deluxe suspension seat with seat belt

- Joystick controls
- Horn and backup alarm
- Gauges and warning lights
- 12 V electrical system
- Lockable doors, covers and toolbox
- Engine block heater
- Rearview mirrors

Options

- Auxiliary hydraulics
- Enclosed all weather cab
- Light package

Attachments

- Standard carriages: 48" (1,22 m), 60" (1,52 m), 72" (1,83 m)
- $\pm 10^\circ$ side tilt carriages: 48" (1,22 m), 60" (1,52 m), 72" (1,83 m)
- $\pm 45^\circ$ swing carriages: 52" (1,32 m) and 72" (1,83 m)
- 48" (1,22 m) pallet forks
- 60" (1,52 m) lumber forks
- 48" (1,22 m) block forks
- 12' (3,7 m) truss boom
- Utility bucket and concrete bucket
- Sheet Material Handler
- Hydraulic earth auger
- 96" Windrow Broom


BACK TO TOP