

Model Info | Load Charts

SKY TRAK 8042 LEGACY MODEL INFORMATION

Engine

Cummins 4BT3.9 Turbo Diesel
110 HP (82 kW) @ 2500 RPM (U/Min)
Torque rating 293 lb. ft. (397 Nm) @ 1500 RPM

Transmission

Modulated powershift, 4-speed forward and 3-speed reverse.

Axles and Brakes

Full-time planetary 4-wheel drive with inboard mounted internal wet disc brakes.

Boom

Telescopic 3-stage welded box section construction using high strength low alloy steel.
Replaceable high density wear pads, to limit friction, with wear indicators.

Operating Specs

Max lift capacity	8000 lbs. (3630 kg)
Lift height	41' 11" (12,7 m)
Max reach below grade	3' 8" (1,1 m)
Operating weight	25,365 lbs. (11,516 kg)
Hydraulic oil capacity	53 gal. (201 liters)
Fuel tank capacity	35 gal. (132 liters)
Standard tires (air filled)	13.0 x 24, 12 ply
Frame tilt to left or right	10°
Top speed	20 mph

Standard Equipment

- TRAK-Attach system
- Automatic fork leveling system
- Frame leveling
- Load holding valves on frame level, stabilizer, attachment tilt, extend and lift cylinders
- Oscillating rear axle with Stabil-TRAK load placement system
- Variable flow, load sensitive hydraulic system
- 2-wheel, 4-wheel and crab steering
- Hydraulically actuated in board wet disc brakes
- Emergency brake with transmission declutch feature
- ROPS/FOPS operator cab

- Deluxe suspension seat with retractable seat belt
- Dual Joystick controls
- Steering wheel mounted horn and backup alarm
- Instrument cluster with gauges and warning lights
- 12 V electrical system
- Lockable doors, covers and tool box
- Engine block heater
- Rear view mirrors

Options

- Auxiliary hydraulics
- Enclosed all weather cab
- Basic work lights
- Complete road lights
- Rotating Beacon
- Fenders
- Soft cab enclosure
- Overnight cab cover
- Cold start package

Attachments

- Standard carriages: 48" (1,22 m), 60" (1,52 m) and 72" (1,83 m)
- $\pm 10^\circ$ side tilt carriages: 48" (1,22 m), 60" (1,52 m) and 72" (1,83 m)
- $\pm 45^\circ$ swing carriages: 52" (1,32 m) and 72" (1,83 m)
- 48" (1,22 m) pallet forks
- 60" (1,52 m) lumber forks
- 48" (1,22 m) block forks
- 12' (3,7 m) truss boom
- Utility bucket
- Wallboard/Sheet material handler
- Hydraulic earth auger
- Concrete bucket
- 96" (2,44 m) Windrow broom


BACK TO TOP