

# SJIII Series

## COMPACTS, CONVENTIONALS AND ELECTRIC DRIVE SCISSOR LIFTS



Versatile. Dependable. Manuverable Industrial and light construction; suitable for congested plant and office areas.

[VIEW PDF](#) [PDF - CE](#) [SPEC CHART](#) [VIDEO](#) [LINE ART](#) [3D / VR](#) [LARGE VIEW](#) [GET INFO](#)

## Features

### Standard Equipment

- Two models to choose from
- Driveable at full height
- 3' (90cm) roll-out deck extension
- Variable speed front wheel hydraulic drive; tight turn radius
- Dual parking brake
- DC power source
- 20% gradeability
- Puncture proof, solid rubber 12x4x8, non-marking tires
- Pothole protection
- Proportional drive and lift controls
- Additional parking brake
- 110V AC GFI protected outlet on platform
- Tilt alarm with drive/lift cutout
- Safety belt lanyard attachments
- Operator horn
- Low voltage battery protection
- All motion alarm

### Optional Equipment

- Flashing amber beacon
- 3' (90cm) Power deck extension

- "Shop Air" line to platform
- 800 Watt AC Generator \*
- "EE" Rated package
- Solid rubber, black tires
- Hinged railing system
- Spring-loaded half height gate \*
- Spring-loaded full height gate

\* Not available for CE Units

## Specifications

<b>Model</b>	<b>SJIII 3015</b>	<b>SJIII 3219</b>
Work Height (Nom.)	21' 6.4m	25' 7.6m
Raised Height (Nom.)	15' 4.6m	19' 5.8m
O/A Width	30.5" .77m	32.5" .83m
O/A Length	66.5" 1.69m	66.5" 1.69m
Stowed Height	78" 1.98m	79" 2.01m
Capacity	500lbs 227kg	500lbs 227kg
Platform Size	27.5" x 64" .70m x 1.63m	27.5" x 64" .70m x 1.63m
Weight	2360lbs 1070kg	2600lbs 1179kg

