

UpRight

SL20

Self-Propelled Lifts



- Narrow electric with 20 ft. platform height, 26 ft. working height
- Dual front wheel direct drive
- 750 lbs. platform capacity
- Smooth, two speed toggle switch controls with ramp on/ramp off
- Driveable with platform fully elevated
- Hydraulically-deployed depression protection system
- Passes through standard doorways without stopping to fold guardrails
- 4 HP DC electric motor
- Non-marking tires

Product Specifications	U.S.	Metric
Working height	26 ft.*	8.10 m*
Platform height (max.)	20 ft.	6.10 m
Driveable height (max.)	20 ft.	6.10 m
Platform capacity (max.)	750 lbs.	340 kgs
Platform size (inside)	29 in. x 131.5 in.	.74 m. x 3.34 m
Gross weight	3,100 lbs.	1,405 kgs
Stowed height	79 in.	2.01 m
Stowed length	107.5 in.	2.73 m
Stowed width	33 in.	0.84 m
Gradeability	25%	14°
Inside turning radius	25 in.	.63 m
Drive speed (max.)	2.3 mph	3.7 km/h
Power source	24V 4HP DC electric motor 4 x 6V 220AH batteries	

N/A - not applicable. Meets or exceeds applicable requirements of OSHA and ANSI A92.6.

Specifications subject to change without notice.

* Working height in the U.S. is 6 ft. above platform height; metric height is 2 meters above platform height.

[[HOME](#) | [PRODUCTS](#)]