

UpRight

SL26N/SL30N

Self-Propelled Lifts



- Working heights of 32 and 36 ft.
- Large, high capacity platform area
- Electric, gasoline, diesel or bi-energy (electric/diesel)
- Proportional drive/lift controls for smooth precise operation
- Ample workspace for people and materials
- Driveable with platform fully elevated

Product Specifications	SL26N	SL30N
Working height	32 ft. (9.77 m.)*	36 ft. (10.99 m.)*
Platform height (max.)	26 ft. (7.77 m.)	29.5 ft. (8.99 m.)
Driveable height (max.)	26 ft. (7.77 m.)	29.5 ft. (8.99 m.)
Platform capacity (max.)	1,300 lbs. (600 kg.)	1,000 lbs. (454 kg.)
Platform size (inside)	57.5 in. x 144 in. (1.46 m. x 3.66 m.)	57.5 in. x 166.25 in. (1.46 m. x 4.23 m.)
Gross weight - gas/diesel	5,100 lbs. (2,315 kg.)	5,410 lbs. (2,455 kg.)
Gross weight - electric	5,160 lbs. (2,345 kg.)	5,470 lbs. (2,485 kg.)
Stowed height	94.5 in. (2.40 m.)	94.5 in. (2.40 m.)
Stowed length	149 in. (3.79 m.)	173 in. (4.39 m.)
Stowed width	66 in. (1.67 m.)	66 in. (1.67 m.)
Gradeability - gas/diesel	30% (16°)	30% (16°)
Gradeability - electric	25% (14°)	25% (14°)
Inside turning radius	9 ft. 9 in. (2.97 m.)	9 ft. 9 in. (2.97 m.)
Drive speed (max.)	3.1 mph. (5.0 km/h.)	3.1 mph. (5.0 km/h.)
Power source	22 HP gas Kohler or 20 HP gas/diesel Kubota or 2 x 24V DC electric motors	

N/A - not applicable. Meets or exceeds applicable requirements of OSHA and ANSI A92.6.

Specifications subject to change without notice.

* Working height in the U.S. is 6 ft. above platform height; metric height is 2 meters above platform height.

[[HOME](#) | [PRODUCTS](#)]

Copyright © 1999 UpRight, Inc.
Last Updated May, 2000