

# UpRight

## SL26SL/SL30SL

### Self-Propelled Lifts



- Fast platform leveling on most uneven ground and slopes
- Working heights of 32 and 36 ft.
- Rough terrain features include 4WD, oscillating front axle, flotation tires
- 35% gradeability
- Proportional drive/lift controls for smooth precise operation
- Gasoline or diesel power
- Patented leveling system

Product Specifications	SL26SL	SL30SL
Working height	32 ft. (9.93 m.)*	36 ft. (11.14 m.)*
Platform height (max.)	26 ft. (7.93 m.)	30 ft. (9.14 m.)
Driveable height (max.)	26 ft. (7.93 m.)	30 ft. (9.14 m.)
Platform capacity (max.)	1,500 lbs. (680 kg.)	1,300 lbs. (590 kg.)
Platform size (inside)	67.5 in. x 144 in. (1.72 m. x 3.66 m.)	67.5 in. x 166.25 in. (1.72 m. x 4.23 m.)
Gross weight - dual fuel	6,130 lbs. (2,780 kg.)	6,380 lbs. (2,894 kg.)
Gross weight - diesel	6,290 lbs. (2,853 kg.)	6,540 lbs. (2,967 kg.)
Stowed height	102.5 in. (2.60 m.)	102.5 in. (2.60 m.)
Stowed length	149 in. (3.79 m.)	173 in. (4.39 m.)
Stowed width	84 in. (2.13 m.)	84 in. (2.13 m.)
Gradeability	35% (19°)	35% (19°)
Inside turning radius	13 ft. (3.96 m.)	13 ft. (3.96 m.)
Drive speed (max.)	3.1 mph. (5.0 km/h.)	3.1 mph. (5.0 km/h.)
Power source	22 HP gas Kohler or gas/diesel Kubota or 22 HP Kubota diesel	

N/A - not applicable. Meets or exceeds applicable requirements of OSHA and ANSI A92.6.

Specifications subject to change without notice.

\* Working height in the U.S. is 6 ft. above platform height; metric height is 2 meters above platform height.

[ [HOME](#) | [PRODUCTS](#) ]

---

Copyright © 1999 UpRight, Inc.  
Last Updated April, 2000